



SAFETY DATA SHEET

Revision Date: 21-Oct-2014

Revision Number: 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name CHLORINATED RUBBER SWIMMING POOL PAINT AQUAMARINE
Product Code CR-2619
Alternate Product Code TR1719
Product Class SOLVENT THINNED PAINT
Color Blue green
Restrictions on use No information available

Manufacturer Benjamin Moore & Co.
101 Paragon Drive , NJ 07645
Phone: 800-225-5554
insl-x.com

Emergency Telephone Number(s)
CHEMTREC (US): 800-424-9300
CHEMTREC (outside US): (703)-
527-3887

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Reproductive toxicity	Category 1B
Aspiration toxicity	Category 1
Flammable liquids	Category 2

Label elements

Danger

Hazard statements

May cause genetic defects
May cause cancer
May damage fertility or the unborn child
May be fatal if swallowed and enters airways
Highly flammable liquid and vapor



Appearance liquid

Odor little or no odor

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Keep away from heat/sparks/open flames/hot surfaces, no smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting/equipment
Use only non-sparking tools
Take precautionary measures against static discharge

Precautionary Statements - Response

If exposed or concerned get medical attention

Skin

If on skin (or hair) take off immediately all contaminated clothing. Rinse skin with water

Ingestion

If swallowed immediately call a POISON CENTER or physician
Do NOT induce vomiting

Fire

In case of fire use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not Applicable

Other information

No information available

3. COMPOSITION INFORMATION ON COMPONENTS

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical Name	CAS-No	Weight % (max)
Xylene	1330-20-7	30
Talc	14807-96-6	15
Chlorinated paraffin	63449-39-8	15
VM&P naphtha	64742-89-8	10
Titanium dioxide	13463-67-7	10
Ethyl benzene	100-41-4	10
Dibutyl phthalate	84-74-2	5
Toluene	108-88-3	1
4,4-isopropylidenediphenol-epichlorohydrin copolymer	25068-38-6	0.5
Silica, crystalline	14808-60-7	0.5

4. FIRST AID MEASURES

First aid measures

General Advice	If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.
Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
Skin Contact	Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
Inhalation	Move to fresh air. If symptoms persist, call a physician. If not breathing, give artificial respiration. Call a physician immediately
Ingestion	Clean mouth with water and afterwards drink plenty of water. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Consult a physician.
Protection Of First-Aiders	Use personal protective equipment
Most Important Symptoms/Effects	No information available.
Notes To Physician	Treat symptomatically

5. FIRE-FIGHTING MEASURES

Flammable Properties	Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause flash fire.
Suitable Extinguishing Media	Foam, dry powder or water. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Protective Equipment And Precautions For Firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Specific Hazards Arising From The Chemical	Flammable. Flash back possible over considerable distance. Keep product and empty container away from heat and sources of ignition. Closed containers may rupture if exposed to fire or extreme heat. Thermal decomposition can lead to release of irritating gases and vapors.
Sensitivity To Mechanical Impact	No
Sensitivity To Static Discharge	Yes
Flash Point Data	
Flash Point (°F)	60.0
Flash Point (°C)	15.6
Flash Point Method	PMCC
Flammability Limits In Air	
Lower Explosion Limit	Not available
Upper Explosion Limit	Not available

NFPA **Health:** 2 **Flammability:** 3 **Instability:** 0 **Special:** Not Applicable

NFPA Legend

- 0 - Not Hazardous
- 1 - Slightly
- 2 - Moderate
- 3 - High
- 4 - Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Remove all sources of ignition. Take precautions to prevent flashback. Ground and bond all containers and handling equipment. Take precautionary measures against static discharges. Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Use personal protective equipment.
Other Information	Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.
Environmental Precautions	See Section 12 for additional Ecological Information.
Methods For Clean-Up	Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

7. HANDLING AND STORAGE

Handling	<p>Avoid contact with skin, eyes and clothing. Wear personal protective equipment. Do not breathe vapors or spray mist. Use only in ventilated areas. Prevent vapor build-up by providing adequate ventilation during and after use.</p> <p>Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Ignition and/or flash back may occur.</p>
Storage	<p>Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children.</p>
Incompatible Materials	No information available
Technical measures/Precautions	<p>Ensure adequate ventilation. Use only where airflow will keep vapors from building up in or near the work area in adjoining rooms. Comply with all national, state, and local codes pertaining to the storage, handling, dispensing and disposal of flammable liquids.</p> <p>Dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. All equipment should be non-sparking and explosion proof. Use explosion proof electrical equipment for ventilation, lighting and material handling.</p>

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits

Chemical Name	ACGIH	OSHA
Xylene	100 ppm - TWA 150 ppm - STEL	100 ppm - TWA 435 mg/m ³ - TWA
Talc	2 mg/m ³ - TWA	20 mppcf - TWA
Chlorinated paraffin	N/E	N/E
VM&P naphtha	N/E	N/E
Titanium dioxide	10 mg/m ³ - TWA	15 mg/m ³ - TWA
Ethyl benzene	20 ppm - TWA	100 ppm - TWA 435 mg/m ³ - TWA
Dibutyl phthalate	5 mg/m ³ - TWA	5 mg/m ³ - TWA
Toluene	20 ppm - TWA	200 ppm - TWA 300 ppm - Ceiling
4,4-isopropylidenediphenol-epichlorohydrin copolymer	N/E	N/E
Silica, crystalline	0.025 mg/m ³ - TWA	respirable - (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable - (250)/(%SiO ₂ + 5) mppcf TWA total dust - (30)/(%SiO ₂ + 2) mg/m ³ TWA

Appropriate engineering controls

Engineering Measures	Ensure adequate ventilation, especially in confined areas.
-----------------------------	--

Personal Protective Equipment

Eye/Face Protection

Safety glasses with side-shields

Skin Protection

Long sleeved clothing. Protective gloves.

Respiratory Protection

Use only with adequate ventilation. In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors.

Hygiene Measures

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	liquid
Odor	little or no odor
Odor Threshold	No information available
Density (lbs/gal)	9.8 - 10.1
Specific Gravity	1.17 - 1.21
pH	No information available
Viscosity (cps)	No information available
Solubility	No information available
Water Solubility	No information available
Evaporation Rate	No information available
Vapor Pressure	No information available
Vapor Density	No information available
Wt. % Solids	45 - 55
Vol. % Solids	30 - 40
Wt. % Volatiles	45 - 55
Vol. % Volatiles	60 - 70
VOC Regulatory Limit (g/L)	< 600
Boiling Point (°F)	240
Boiling Point (°C)	116
Freezing Point (°F)	No information available
Freezing Point (°C)	No information available
Flash Point (°F)	60.0
Flash Point (°C)	15.6
Flash Point Method	PMCC
Flammability (solid, gas)	Not available
Upper Explosion Limit	Not available
Lower Explosion Limit	Not available
Autoignition Temperature (°F)	No information available
Autoignition Temperature (°C)	No information available
Decomposition Temperature (°F)	No information available
Decomposition Temperature (°C)	No information available
Partition Coefficient (n-octanol/water)	No information available.

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical Stability	Stable under normal conditions. Hazardous polymerisation does not occur.
Conditions To Avoid	Keep away from open flames, hot surfaces, static electricity and sources of ignition. Sparks. Elevated temperature.
Incompatible Materials	Incompatible with strong acids and bases and strong oxidizing agents.
Hazardous Decomposition Products	Thermal decomposition can lead to release of irritating gases and vapors.
Possibility Of Hazardous Reactions	None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product

Repeated or prolonged exposure to organic solvents may lead to permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

Inhalation	No information available
Eye contact	No information available
Skin contact	No information available
Ingestion	No information available

Acute Toxicity

Product	No information available
----------------	--------------------------

Information on toxicological effects

Symptoms	No information available
-----------------	--------------------------

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization:	Not available
Mutagenic Effects	Not available
Reproductive Effects	No information available

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	9784 mg/kg
ATEmix (dermal)	8341 mg/kg
ATEmix (inhalation-dust/mist)	179 mg/L

Acute Toxicity

Component

Xylene

LD50 Oral: 4300 mg/kg (Rat)

LD50 Dermal: > 1700 mg/kg (Rabbit)
LC50 Inhalation (Vapor): 5000 ppm (Rat, 4 hr.)

Chlorinated paraffin

LD50 Oral: 26100 mg/kg (Rat)
LD50 Dermal: > 10 mL/kg (Rabbit)

Titanium dioxide

LD50 Oral: > 10000 mg/kg (Rat)
LD50 Dermal: > 10000 mg/m³ (Rabbit)
LC50 Inhalation (Dust): > 6.82 mg/L (Rat, 4 hr.)

Ethyl benzene

LD50 Oral: 3500 mg/kg (Rat)
LD50 Dermal: > 5000 mg/kg (Rabbit)
LC50 Inhalation (Vapor): 55000 mg/m³ (Rat, 2 hr.)

Dibutyl phthalate

LD50 Oral: 7,499 mg/kg (Rat)
LD50 Dermal: > 20 mL/kg (Rabbit)
LC50 Inhalation (Vapor): 4,250 mg/m³ (Rat)

Toluene

LD50 Oral: 636 mg/kg (Rat)
LD50 Dermal: 14100 µL/kg (Rabbit)
LC50 Inhalation (Vapor): 49000 mg/m³ (Rat, 4 hr.)

4,4-isopropylidenediphenol-epichlorohydrin copolymer

LD50 Oral: 11,400 mg/kg (Rat)

Silica, crystalline

LD50 Oral: 500 mg/kg (Rat) vendor data

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:

Chemical Name	IARC	NTP	OSHA Carcinogen
Chlorinated paraffin	2B - Possible Human Carcinogen		Listed
Titanium dioxide	2B - Possible Human Carcinogen		Listed
Ethyl benzene	2B - Possible Human Carcinogen		Listed
Silica, crystalline	1 - Human Carcinogen	Known Human Carcinogen	Listed

- Crystalline Silica has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.
- Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

Product

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available

Bioaccumulation / Accumulation

No information available

Mobility in Environmental Media

No information available

Ozone

Not Applicable

Component

Acute Toxicity to Fish

Xylene

LC50: 13.5 mg/L (Rainbow Trout - 96 hr.)

Titanium dioxide

LC50: >1000 mg/L (Fathead Minnow - 96 hr.)

Ethyl benzene

LC50: 12.1 mg/L (Fathead Minnow - 96 hr.)

4,4-isopropylidenediphenol-epichlorohydrin copolymer

LC50: 1.5 mg/L (Rainbow Trout - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

Ethyl benzene

EC50: 1.8 mg/L (Daphnia magna - 48 hr.)

Acute Toxicity to Aquatic Plants

Ethyl benzene

EC50: 4.6 mg/L (Green algae (Scenedesmus subspicatus), 72 hrs.)

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

Empty Container Warning

Emptied containers may retain product residue. Follow label warnings even after container is emptied. Residual vapors may explode on ignition.

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name	Paint (Mixture)
Hazard Class	3
UN-No	UN1263
Packing Group	II

ICAO / IATA

Contact the preparer for further information.

IMDG / IMO

Contact the preparer for further information.

15. REGULATORY INFORMATION

International Inventories

United States TSCA

Yes - All components are listed or exempt.

Canada DSL

Yes - All components are listed or exempt.

Federal Regulations

SARA 311/312 hazardous categorization

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight % (max)
Xylene	1330-20-7	30
Ethyl benzene	100-41-4	10
Dibutyl phthalate	84-74-2	5
Toluene	108-88-3	1

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

Chemical Name	CAS-No	Weight % (max)
Xylene	1330-20-7	30
Ethyl benzene	100-41-4	10
Dibutyl phthalate	84-74-2	5
Toluene	108-88-3	1

State Regulations

California Proposition 65

This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.

State Right-to-Know

Chemical Name	Massachusetts	New Jersey	Pennsylvania
Xylene	X	X	X
Talc	X	X	X
Chlorinated paraffin	X		
Titanium dioxide	X	X	X
Ethyl benzene	X	X	X
Dibutyl phthalate	X	X	X
Toluene	X	X	X
Silica, crystalline	X	X	X

Legend

X - Listed

16. OTHER INFORMATION

HMIS

Health: 2*

Flammability: 3

Reactivity: 0

PPE: -

HMIS Legend

0 - Minimal Hazard
1 - Slight Hazard
2 - Moderate Hazard
3 - Serious Hazard
4 - Severe Hazard
* - Chronic Hazard
X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By Product Stewardship Department
Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
855-724-6802

Revision Date: 21-Oct-2014
Revision Summary Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

END OF SAFETY DATA SHEET