

Low profile recessed down light (package of 6) 297735/298614/305968/306365

Features

Low profile recessed down light. Can be used in various applications including corridors, closets, bath, hallway, kitchen or anywhere general lighting is needed.

Construction

Spring mounted. Extends only .17" from celiling. Mounting template included. Power supply connections are made inside the remote driver box.

Finish

White or Matte Black housing.

Diffuser

White acrylic diffuser.

Electrical

Direct wire to remote driver rated for 120 VAC. The driver is dimmable down to 10% of full scale with a 2-wire (TRIAC) or electronic low voltage (ELV) dimmer switch.

LED

Integrated LED modules capable of producing: 10W = 600 delivered lumens 13W = 800 delivered lumens 18W = 1300 delivered lumens 2700/3000K/3500/4000K/5000K Adjustable CCT Rated for 50.000 Hrs., 90 CRI.

Certification:

cETLus listed for indoor damp locations.

IC rated

Wet location rated for indoor use. Outdoor wet location rated for covered ceiling mount applications ONLY (not recommended for any other outdoor use). Suitable for use in clothes closets when installed in accordance with the NEC 410.16 spacing requirements.

Limited Warranty:

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	


















Ordering Information:

	Delivered						
White	Matte Black	LED	Lumens	Adjustable CCT	DIA.	D	
297735 (Equivalent to a 4" can)		10W	700	2700K/3000K/3500K/4000K/5000K	5"	1"	
305968 (Equivalent to a 6" can)	298614 (Equivalent to a 6" can)	13W	800	2700K/3000K/3500K/4000K/5000K	6-7/8"	1"	
306365		18W	1300	2700K/3000K/3500K/4000K/5000K	8-3/4"	1"	



Exclusively Distributed By: HD Supply 3400 Cumberland Blvd. SE Atlanta, GA 30339 HD Supply is here to help.
Online Chat: hdsupplysolutions.com
Email: customercare@hdsupply.com
Call: 1-800-431-3000