

# MATERIAL SAFETY DATA SHEET

## I. PRODUCT IDENTIFICATION

Name: HENRY 430 "ClearPro" Thin Spread Floor Tile Adhesive  
Description: Water dispersed latex adhesive

## II. DEPARTMENT OF TRANSPORTATION INFORMATION

SHIPPING NAME: Not classified Hazard Class: N/A ID#: N/A  
EMERGENCY ONLY CONTACT: CHEM TEL 1-800-255-3924

## III. HMIS (0=Minimal hazard; 4=severe hazard)

Health = 1 Flammability = 1 Reactivity = 1

## IV. PRODUCT CONTENT

This product does not contain chemicals subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR 372. All components are on TSCA inventory. This product does not contain asbestos.

## V. HAZARDOUS INGREDIENTS

INGREDIENT: None

PERCENT:

OCCUP. EXPOS. LMT.

## VI. PHYSICAL DATA

APPEARANCE: Beige creamy paste. ODOR: Mild odor.  
BOILING POINT: 212°F. MELTING POINT: N/A. VAPOR  
PRESSURE: (mm Hg @ 20°C): N/K. VAPOR DENSITY: (air =  
1): N/K. % VOLATILE BY WEIGHT (30 min. @ 275°F): 56.0 -  
58.0 %. EVAPORATION RATE: (butyl acetate = 1): N/K.  
WT/GAL (water=8.3): 8.37 lb. SOLUBILITY IN WATER:  
Dispersible. SPECIFIC GRAVITY: 1.00. VOC: 0 g/l calculated at  
70°F/21°C, SCAQMD. pH: 9.2.

## VII. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD): > 200° F (Setaflash Closed Tester).  
FLAMMABLE RANGE: LEL: N/A; UEL: N/A. EXTINGUISHING  
MEDIA: Carbon dioxide, dry chemical, or water spray. SPECIAL  
FIRE FIGHTING PROCEDURES: Protect fire fighters from toxic  
products of combustion by wearing self-contained breathing  
apparatus. UNUSUAL FIRE AND EXPLOSION HAZARDS:  
Closed containers in a fire may rupture due to pressure build-up;  
use water to cool containers to prevent this.

## VIII. HEALTH HAZARD DATA

PRIMARY ROUTE(S) OF ENTRY: N/A TARGET ORGANS: N/A  
EFFECTS OF OVEREXPOSURE: SKIN AND EYES: May  
produce slight transient irritation to the eyes. INHALATION: N/A  
CARCINOGENICITY: NTP: No. IARC Monographs: No. OSHA  
Regulated: No. MEDICAL CONDITIONS GENERALLY  
AGGRAVATED BY EXPOSURE: None. FIRST AID  
PROCEDURES: SKIN AND EYES: Flush any eye contact with  
plenty of water. Additionally with skin contact, wash with soap  
and water. Refer to physician if irritation or symptoms persist.  
INHALATION: Remove to fresh air if exposed to excess  
concentrations of vapor. Seek medical attention if symptoms  
persist. INGESTION: Do not induce vomiting. Call a Poison  
Control Center or physician for guidance.

## IX. REACTIVITY DATA

STABILITY: Stable. INCOMPATIBILITY: Strong oxidizing  
agents. HAZARDOUS DECOMPOSITION PRODUCTS: Carbon  
monoxide, carbon dioxide, and other toxic vapors and gases that

# HENRY®

## 430

**Prepared 7/06 – Replaces 11/98**

The W.W. Henry Company  
400 Ardex Park Drive  
Aliquippa, PA 15001  
(724) 203-8499

are common to thermal degradation of organic compounds.  
HAZARDOUS POLYMERIZATION: Will not occur.

## X. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR  
SPILLED: Ventilate area of spill or release. Contain spill,  
preventing it from entering sewer lines or waterways. Use  
absorbent to assist with the pick-up of material. Scrape up  
product and place into container. Residual of product, while still  
wet, can be cleaned up with warm soapy water. WASTE  
DISPOSAL METHOD: Dispose of container and any unused  
contents in accordance with Federal, State, and Local Waste  
Disposal Regulations. Do not flush unused contents or residue  
down drains. Do not reuse container.

## XI. SAFE HANDLING AND USE INFORMATION

VENTILATION: Use natural cross-ventilation, local (mechanical)  
pick-up, and/or general area (mechanical) ventilation.  
RESPIRATORY PROTECTION: Should not be needed. SKIN  
AND EYE PROTECTION: During normal end-product use, cotton  
or loop-pile gloves and spectacle-type safety glasses are  
recommended to prevent contact with this mastic product.

## XII. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:  
Recommended storage temperature is below 90° F. OTHER  
PRECAUTIONS: None. WORK SITE ENVIRONMENT: Initially  
there may be a potential adverse impact on indoor air quality  
within the general work area during the installation process.  
Therefore you should advise the building manager or other  
appropriate person that: • It will be necessary to establish and  
maintain adequate ventilation of the work area, without causing  
the entry of contaminants to other parts of building; and • Persons  
who are sensitive to odors and/or chemicals should be advised to  
avoid the work area during this process.

The information presented herein is supplied as a guide to those  
who handle or use this product. Safe work practices must be  
employed when working with any materials. It is important that  
the end user makes a determination regarding the adequacy of  
the safety procedures employed during the use of this product.